



Application

- Suitable for all gaseous and liquid media that will not obstruct the pressure system or attack copper alloy parts.
- Pneumatics.
- Heating, ventilation, air-conditioning.
- General industry.

Specification

Nominal Size	4" (100mm)
Casing	Black Finish Steel
Window	Glass / Plastic (Polycarbonate)
Dial	White Aluminum, Double Scales
Movement	Brass
Bourdon Tube	Phosphor Bronze
Connection	Bottom Entry
Thread	3 / 8" (10mm) BSPT
Pointer	Black Aluminum
Accuracy	+/- 1.5%
Range	76cm Hg Vac to 400 psi (-1 bar to 28 bar) (other range available upon request)

Operating Temperature

Ambient	-40° C to +60° C
Medium	+60° C maximum

* We reserve the right to alter specifications or dimensions without prior notice.

Distributed By:



Maxwell Valve Industry Sdn Bhd
Vess Valve Sdn. Bhd. (922423-U)
 No. 26, Jalan Utama 2/28,
 Taman Perindustrian Puchong Utama,
 47140 Puchong, Selangor Darul Ehsan, Malaysia.

Tel : 60(3) 8060 3325
 Fax : 60(3) 8060 3341
 E-mail : sales@maxwellvalve.com
 Web : www.maxwellvalve.com