



Application

- Suitable for all gaseous and liquid media that will not obstruct the pressure system or attack copper alloy parts.
- Pneumatics.
- Heating , ventilation , air-conditioning.
- General industry.

Specification

Normal Size	4 " (100mm)
Casing	Stainless Steel 304
Window	Glass
Dampening Fluid	Glycerine
Dial	White Aluminium , Double Scales
Movement	Brass
Bourdon Tube	Phosphor Bronze
Connection	Bottom Entry
Thread	3 / 8 " (10mm) BSPT
Pointer	Black Aluminium
Accuracy	+/- 1.5%
Range	0 to 300 psi (0 to 20 bar) (Other range available upon request)

Operating Temperature

Ambient	- 40°C ~ 60° C
Medium	60°C maximum

** We reserve the right to alter specifications or dimensions without prior notice.*

Distributed By :



Maxwell Valve Industry Sdn Bhd

Vess Valve Sdn Bhd (799530-K)
(922423-U)

No.26 , Jalan Utama 2/28 ,
Taman Perindustrian Puchong Utama,
47140 Puchong , Selangor Darul Ehsan , Malaysia

Tel : 60(3) 8060 3325

Fax : 60(3) 8060 3341

E-mail : sales@maxwellvalve.com

Web : www.maxwellvalve.com