



Headloss Chart

### Pressure & Temperature

Nominal Pressure	16 bar
Hydraulic Shell Test Pressure	24 bar
Hydraulic Seat Test Pressure	17.6 bar
16 Bar at	-10° to 100° C
Suitable Medium	Water

### Specification

Low Headloss	Spring Closing System
Maximise Flow	Operating In Any Position
Epoxy Coating	Flanges To BS4504 PN 16

### Material Specification

Component	Material	Specification
Body	Cast Iron	BS 1452 Gr 250
Guide	Ductile Iron	BS 2789 Gr 500
Closing System	Bronze / Ductile Iron	BS 1400 LG-2 / BS 2789 Gr 500
Guiding Stem	Bronze	BS 1400 LG-2
Springs	Stainless Steel	BS 970 431
Seal	NBR / EDPM	-
Bushing	Bronze	BS 1400 LG-2

**Note:**

1. Other flange types available, specify on order.

### Dimensions - Millimetres

Size (DN)	50	65	80	100	125	150	200	250	300
A	100	120	140	170	200	230	300	370	410
B	165	185	200	220	250	285	340	405	460

\* We reserve the right to alter specifications or dimensions without prior notice.

Distributed By:



**Maxwell Valve Industry Sdn. Bhd.**  
 No. 26, Jalan Utama 2/28,  
 Taman Perindustrian Puchong Utama,  
 47100 Puchong, Selangor Darul Ehsan, Malaysia

Tel : 60(3) 8060 3325  
 Fax : 60(3) 8060 3341  
 Email : sales@maxwellvalve.com  
 Web : www.maxwellvalve.com